

Data Cables

U / UTP Cat6

Ref. Std. ANSI/TIA/EIA 568-B.2-ISO/IEC 11801-EN 50173/TS IEC 61156-5

Dahili Tesisat LAN Kablosu

LAN Cable for Internal Installation



Kablo Yapısı / Construction

İç İletken Inner Conductor	Elektrolitik mono tavlı bakır (EN 60228, sınıf 1)AWG23/24 Electrolytic mono annealed copper (EN 60228, class1) AWG24	Dış Kılıf Outer Sheath	PVC (EN 50290-2-22) HFFR (EN 50290-2-27)
İzolasyon Insulation	Solid PE (EN 50290-2-23, VDE 0207-2Y11) damar renkleri IEC 189 a uygun olacaktır . Core Colors will be appropriate according to IEC 189.	Kılıf Rengi Sheath Color	PVC: RAL 7035, Gri PVC: RAL 7035, Gray
Öz Oluşturma Lay-Up	Damarlar çiftler halinde ve tüm çiftler seperatör ile bir arada bükülür. Cores are twisted in pairs, and all the pairs are twisted with seperator.		

Genel Özellikler - General Features

- ✓ **Alev Testi / Flame Test**
IEC 60332-1, EN 60332-1, VDE 0482-332-1
- ✓ **Halojen-Korozif Gaz Testi / Halogen-Corrosive Gas Test**
IEC 60754-2, EN 50267-2, VDE 0482-267-2 (HFFR)
- ✓ **Duman Yoğunluğu / Smoke Density**
IEC 61034-2, EN 61034-2, VDE 0482-1034-2 (HFFR)

Kullanım Alanı

Terminal yoğunluğu fazla olan ofisler,yönetim,AR-GE binalarında kablolar, bilgi iletişim sistemlerinde sinyal iletiminde kullanılırlar. ISDN, Ethernet 10 Base-T, Fast Ethernet 100 Base-T, Gigabit Ethernet 1000 Base-T, Token Ring 4/16 Mbit/s, TP-PMD/TP-DDI 125 Mbit/s, ATM 155 Mbit/s sistemlerini destekler.

Application

Such cables are used for the connections of data communication systems. These cables which are designed for transmitting digital and analog voice, data and video signals; also support; ISDN, Ethernet 10 Base-T, Fast Ethernet 100 Base-T, Gigabit Ethernet 1000 Base-T, Token Ring 4/16 Mbit/s, TP-PMD/TP-DDI 125 Mbit/s, ATM 155 Mbit/s systems.

Elektriksel Özellikler / Electrical Characteristics

20 °C

İletken Çevrim Direnci (Ω/Km) Conductor Loop Resistance	176 Ω.Km
Karakteristik Empedans (1-16 MHz) Characteristic Impedance	100±15 Ω
Efektif Kapasite Effective Capacity	Max. 52 pF/m
Yayıma Hızı Velocity of Propagation	%67
İzolasyon Direnci (M.Ω.Km) Insulation Resistance	>5000

Data Cables

U / UTP Cat6

Ref. Std. ANSI/TIA/EIA 568-B.2-ISO/IEC 11801-EN 50173/ TS IEC 61156-5

Dahili Tesisat LAN Kablosu

LAN Cable for Internal Installation

Teknik Özellikler / Technical Properties

Çalışma Sıcaklığı (°C) Temperature Range	20 °C
	-20 °C +60 °C
Çalışma Gerilimi Test Voltage	72 V DC max
Test Gerilimi Test Voltage	1500 V
Min. Bükme Yarıçapı (mm) Min. Bending Radius	8xD

Tablo - 1 / Table - 1

IEC 189 'a Göre Damar Renkleri/ IEC 189 'According To Wire Colors

No.	A – Teli A - Wire	B – Teli B - Wire
1.	Mavi/Blue	Mavi/Beyaz Blue/White
2.	Portakal/Orange	Portakal/Beyaz Orange/White
3.	Yeşil/Green	Yeşil/Beyaz Green/White
4.	Kahverengi/Brown	Kahverengi/Beyaz Brown/White

Tablo - 2 / Table - 2

Kablo Tipi Cable Type	Ort. Çap (mmØ) Avg. Diameter(mmØ)	Ort. Ağırlık (Kg/Km) Nom.Weight (Kg/Km)	Standart Ambalaj Standart Package	Kod No Code
U/UTP Cat 6	6,2	50	305/500/1000	531570043
U/UTP Cat 6 HFFR	6,2	50	305/500/1000	531571043

Tablo - 3 / Table - 3

Frekans Frequency	Zayıflama Attenuation	Yakın Uç Diafonisi Near-End Crosstalk Next	Geri Dönüş Kaybı Return Loss
	dB/100m	dB (min)	dB (max)
4 MHz	3,6	71	27
10 MHz	5,7	65	27
20 MHz	8,3	61	27
62,5 MHz	14,8	53	25,8
100 MHz	19	50	25
250 MHz	31	44	22
350 MHz	34	43	22